

- ???????

S60 3rd Edition

- ????

Symbian OS v9.1 ??????API?????????????????POP3?IMAP4?????????CEmailAccount
API?????????????SMTP????????????????????

????????API?????

```
#include <cemailaccounts.h>

TMsvId pop3Id;

TMsvId smtpId;

iPop3Mtm = static_cast<CPop3ClientMtm*>(iReg->NewMtmL(KUIdMsgTypePOP3));
iSmtpMtm = static_cast<CSmtpClientMtm*>(iReg->NewMtmL(KUIdMsgTypeSMTP));

CEmailAccounts* accounts = CEmailAccounts::NewLC();

//

// Create CImPop3Settings and CImSmtpSettings objects and insert your account settings.
// This step is omitted here for brevity.

//

//

// You also need to define a CImIAPPreferences object for the IAP to use with this account.
// This example does not show how to fill in the IAP UID into apUid. One possibility is to read t
// CommsDB IAP table by a bearer.

//

TUint32 apUid;

// Create a new IAPChoice for the IAPPreferences object

TImIAPChoice apChoice;

apChoice.iIAP = apUid; //store IAP id

apChoice.iDialogPref = ECommDbDialogPrefPrompt; //prompt dialog

//CImIAPPreferences*

apPrefs = CImIAPPreferences::NewLC();

apPrefs->AddIAPL(apChoice);
```

å "ä»£ç ä,-ç æ ç µå- é ®ä»¶å, æ .

```
// Now create actual services
//
TPopAccount popAcc;
popAcc = accounts->CreatePopAccountL(_L("POP3 acco"), *iPOP3Settings, *apPrefs, EFalse);
TSmtpAccount smtpAcc;
smtpAcc = accounts->CreateSmtpAccountL(popAcc, *iSmtpSettings, *apPrefs, EFalse);
pop3Id = popAcc.iPopService;
smtpId = smtpAcc.iSmtpService;
//
// Finally, this line sets the new SMTP service as the default sending service.
//
accounts->SetDefaultSmtpAccountL(smtpAcc);
```