



An active object is an object of a CActive-derived class. It uses an asynchronous service-provider to make an asynchronous service available to clients. An active object provides methods to issue a request to the service provider, get a notification when the request completes and to cancel the outstanding request. Below is an example of a simple active object.

Contents

- [1](#)
[MyActiveObject.h](#)
- [2](#)
[MyActiveObject.cpp](#)
- [3 Internal](#)
[Links](#)
- [4 External](#)
[Links](#)

MyActiveObject.h

```
#ifndef __MYACTIVEOBJECT_H__
#define __MYACTIVEOBJECT_H__
```

CActive class is declared in e32base.h so we need to include this header.

```
#include <e32base.h>
```

CActive class is Link against: euser.lib so we need to include this library to .mmp file.

```
LIBRARY                euser.lib
```

Observer class to handle the async request result.

```
class MMyActiveObjectObserver
{
public:
```

Pure virtual function that shall be implemented by every user of CMyActiveObject object. It is called when async service provider completes the request.

```
virtual void HandleRequestCompleted(TInt aError) = 0;
};
```

Active object that utilizes the use of RMyAsyncServiceProvider.

```
class CMyActiveObject : public CActive
{
public:
static CMyActiveObject* NewL(TInt aPriority);
    ~CMyActiveObject()

void DoAsyncAction(MMyActiveObjectObserver* aObserver);
```

Active_object

```
protected:
// inherited from CActive
void RunL();
void DoCancel();
    TInt RTimeError;

private:
    CActiveObjectPriority);
void ConstructL();

private:
// Provide your own service provider object e.g. RTimer here
    RMyAsyncServiceProvider iServiceProvider;

    MMyActiveObjectObserver; // Observer
};

#endif // __MYACTIVEOBJECT_H__
```

MyActiveObject.cpp

```
#include "myactiveobject.h"
```

A factory function to create our active object. See [Two-phase construction](#). The active object's priority is passed as the param, see [CActive::TPriority](#) for possible priority values.

```
CMyActiveObject* CActiveObject::NewL(TInt aPriority)
{
    CActiveObject new (ELeave) CActiveObject(aPriority);
    CleanupStack(self);
    ->ConstructL();
    CleanupStack
return self;
}
```

Constructor. It is called from our NewL () function. Here we set active object's priority; it is done only once, you cannot change active object's priority then.

```
CMyActiveObject::CMyActiveObject(TInt aPriority)
: CActive(aPriority)
{
}
```

Initialize our active object.

```
void CActiveObject::ConstructL()
{
```

Add the active object to the [Active Scheduler](#). If we do not do this we will end up with the E32User-CBase [panic](#) when our async request completes. CActiveScheduler::Add() method is [leave](#)-safe so actually it can be called in active object's constructor.

```
CActiveScheduler::Add(this);
```

Any necessary code to initialize the async service provider, [leave](#) in case of an error. for example, if

Active_object

initialization is through a Connect() method that returns a TInt error:

```
User::LeaveIfError(iServiceProvider.Connect());
}
```

Destructor.

```
CMyActiveObject::~CMyActiveObject()
{
```

Cancel () should be always called in active object's destructor to cancel an outstanding request if there is one. If there is no request pending then Cancel () just does nothing, but if we do not call Cancel () when having an outstanding request E32User-CBase panic 40 will be raised.

```
Cancel();
```

Close the session to our async service provider (as you would do in any destructor).

```
iServiceProvider.Close();
}
```

This method is called by our active object users to start an async action. The argument is a pointer to an observer object who's HandleRequestCompleted () method will be called when the async request completes.

```
void CMyActiveObject::DoAsyncAction(MMyActiveObjectObserver* aObserver)
{
```

Assert that we do not have an outstanding request already and panic if we have. If we do not do this checking then SetActive () will raise E32User-CBase 42 panic. See Panic for information about asserts and panics.

```
__ASSERT_ALWAYS(!IsActive(), User::Panic(KMyActivePanic, EAlreadyActive));
```

Assert that aObserver is not NULL.

```
__ASSERT_ALWAYS(aObserver, User::Panic(KMyActivePanic, ENoObserver));
```

Issue a request to our service provider. We pass our iStatus as the argument. The service provider sets our iStatus to KRequestPending. When the service provider finishes its work Active Scheduler will complete the iStatus with the error code indicating if the operation was successful or not.

```
iServiceProvider.DoService(iStatus);
```

Mark our active object as active which means that we are waiting for our outstanding request to complete.

```
SetActive();
}
```

RunL () is called by the Active Scheduler when our request is completed. All active objects need to implement this function. Active Scheduler runs RunL () under a trap harness. If it leaves active object's RunError () is called.

```
void CMyActiveObject::RunL()
{
```

Active_object

iStatus contains the error code indicating if our request completed successfully or not. We leave if there is an error.

```
User::LeaveIfError(iStatus.Int());
```

If we reached here it means that our request completed successfully - let's tell the observer about it.

```
iObserver->HandleRequestCompleted(KErrNone);  
}
```

Every active object shall implement this function. DoCancel() is called as part of the active object's Cancel() and shall cancel the outstanding request.

```
void CMyActiveObject::DoCancel()  
{  
    iServiceProvider->Cancel();  
}
```

It is not necessary to implement RunError() function but it is very useful to do it. It is called by the Active Scheduler if a leave occurs in active object's RunL(). The overridden implementation should handle the error (if possible) and always return KErrNone. If RunError() is not implemented by the active object then the default version is called that just returns the leave code (aError). If RunError() returns anything but KErrNone Active Scheduler calls its Error() function. If CActiveScheduler::Error() is not overridden by a CActiveScheduler-derived class which is usually not the case then the default implementation of CActiveScheduler::Error() raises E32USER-CBase 47 panic.

```
TInt CMyActiveObject::RunError(TInt aError)  
{
```

Inform our observer about the error so that it can handle it like performing recovery actions or issuing another async request. RunError() should be leave-safe so we run HandleRequestCompleted() under a trap harness. A callback should never leave.

```
iObserver->HandleRequestCompleted(aError);  
return KErrNone;  
}
```

Internal Links

[Active Objects in Symbian OS](#)

[Responsibilities of Asynchronous Service Provider in Active Objects](#)

External Links

[CActive](#) in Symbian OS Developer Library

[CActiveScheduler](#) in Symbian OS Developer Library