



Headers required:

```
#include <f32file.h>
#include <apgcli.h>
#include <apacmdl.h>
```

Library needed:

```
LIBRARY efsrv.lib
LIBRARY apgrfx.lib
LIBRARY apparc.lib
```

Source:

```
_LIT(KAppPath, "c:\\system\\apps\\appname\\myapp.app");
_LIT(KParameters, "somearguments");

RFs fs;
User::LeaveIfError(fs.Connect());
CleanupClosePushL(fs);
TFindFile file(fs);
User::LeaveIfError(file.FindByDir(KAppPath, KNullDesC));

RApaLsSession ls;
User::LeaveIfError(ls.Connect());
CleanupClosePushL(ls);
CApaCommandLine *cmd = CApaCommandLine::NewLC();
cmd->SetLibraryNameL(file.File());
// Passing parameters //
cmd->SetTailEndL(KParameters);
cmd->SetCommandL(EApaCommandRun);
User::LeaveIfError(ls.StartApp(*cmd));

CleanupStack::PopAndDestroy(3);
```

Internal Links:

- [How to Launch Browser in 3rd edition](#)
- [How to get ReDraw event in exe from window server?](#)
- [How to capture Keyevents in thread or exe](#)
- [Graphics in EXE](#)
- [How to start EXE from an EXE in 3rd Edition](#)